

EX3

TRADITIONAL ESPRESSO

EX3

Versions

- EX3 MINI 1GR
- EX3 MINI 2GR
- EX3 2GR
- EX3 3GR



Features



Control



Display (PID controlled)



TA (Take Away)/High Group

Crem EX3 is an attractive and extremely versatile professional espresso machine. Featuring a smart design concept it can be easily customized, and manufactured through the **combination of numerous different options**, both external (number of groups, colours and finishings, lighting, etc.) and technical. Thus, the EX3 is aimed to suit any kind of business with an espresso demand, whatever it is an independent or a national coffee shop chain.

Ergonomics and user experience have been also key on this project. Following Crem's standards of performance, the EX3 features **our highly tested technologies** in order to deliver a superior in cup quality.

Main USP's & advanced features

- Optimized and stylish design line
- Wide range of external and technical customizable options
- Crem's highly tested hydraulics, including:
 - 1/2 rotatory knobs
 - Cool touch wands
 - Improved drainage solution
- Ease-of-servicing

CREM *Tech* inside



Please check **EX3 PRODUCT CONFIGURATOR** to preview available options

Options & Extras

- Keypad: Control or Display (PID controlled)
- Group height: Standard or Take Away (High group)
- Pressure gauge: Single or Double.
- Steam / Levers and HW controls: All available in black, white or wooden (oak, walnut) finishings. Extra wand (except Mini 1GR)
- Colours: A wide range of colour and combinations available.
- Body covers: Oak, walnut, brushed aluminium
- Barista lights.
- High feet / Hidden feet


Technical specifications



	EX3 3GR	EX3 2GR	EX3 MINI 2GR	EX3 MINI 1GR
Height, width, depth	465, 990, 575 mm 18.3, 39, 22.6"	465, 770, 575 mm 18.3, 30.3, 22.6"	465, 550, 575 mm 18.3, 21.6, 22.6"	465, 550, 575 mm 18.3, 21.6, 22.6"
Weight	74 Kg 163 lb	62 Kg 136.7 lb	50 Kg 110.2 lb	48 Kg 105.8 lb
Power ratings <i>(Power ratings+OPTIONS)</i>	380-415V 2N~ 4350W 50-60Hz (O) 380-415V 3N~ 6350W 50-60 Hz (O) 220-240V~ 4350W 50-60Hz	220-240V~ 3350W 50-60Hz (O) 3Ph: 380-415V 3N~ 4800W 50-60 Hz	220-240V~ 2800W 50-60Hz (O) 220-240V~ 2300W 50-60Hz	220-240V~ 2800W 50-60Hz (O) 220-240V~ 2300W 50-60Hz
Boiler(s) capacity	17.5 l	11.5 l	6 l	6 l
Operation pressure	0.8 to 1.2 bar	0.8 to 1.2 bar	0.8 to 1.2 bar	0.8 to 1.2 bar
Pressure switch control	✓	✓	✓	✓
PID control	(O) 220-240V~ 4350W 50-60Hz	○	○	○
Water connection	3/8" Internal thread	3/8" Internal thread	3/8" Internal thread	3/8" Internal thread
Height group	STD / TA (O)	STD / TA (O)	STD / TA (O)	STD / TA (O)
Volumetric dosing (5 keypad button)		✓	✓	✓
Volumetric dosing + group display	✓	○	○	○
Group flush button	✓	✓	✓	✓
Steam wands + HW tap	2+1	1+1	1+1	1+1
Extra steam wand	✓	✓(1)	✓(1)	-
Auto hot tap water dose	○	○	○	-
½ turn rotary taps	✓	✓	✓	✓
Lever taps	○	○	○	-
Cool touch steam wands	✓	✓	✓	✓
Built-in rotatory pump	✓	✓	✓	✓
Pre infusion chamber group head	✓	✓	✓	✓
Electronic pre infusion	✓	✓	✓	✓
Jet hole	STD group height: 3.5 / 2.5 mm (O) TA group: 2.5 mm	STD group height: 3.5 / 2.5 mm (O) TA group: 2.5 mm	STD group height: 3.5 / 2.5 mm (O) TA group: 2.5 mm	STD group height: 3.5 / 2.5 mm (O) TA group: 2.5 mm
Pressure gauge	60 mm single / double (O)	60 mm single / double (O)	60 mm single / double (O)	60 mm single / double (O)
Hidden feet	○ White, black, stainless steel (only available for STD height group versions)	○ White, black, stainless steel (only available for STD height group versions)	○ White, black, stainless steel (only available for STD height group versions)	-
Colours	STD: White, black, red	STD: White, black, red	STD: White, black, red	STD: White, black, red
Knob /levers finishing	STD: white, black O: Oak, Walnut	STD: white, black O: Oak, Walnut	STD: white, black O: Oak, Walnut	STD: White, Black O: Oak, Walnut"
Body covers	O: Oak, walnut, aluminium	O: Oak, walnut, aluminium	O: Oak, walnut, aluminium	O: Oak, walnut, aluminium
Barista lights	○	○	○	○
Auto cleaning group cycle	✓	✓	✓	✓
ECO mode	✓	Only for PID versions	Only for PID versions	Only for PID versions
Auto On/OFF	✓	Only for PID versions	Only for PID versions	Only for PID versions
Power cord (Country Kit)	STD: BareW	STD: Type F (1Ph) or BareW (3Ph) O: Only for 1Ph (Type I 15A, 16A BareW)	STD: Type F O: Only for 1Ph (Type I 10A, Type G 13A)	STD: Type F O: Only for 1Ph (Type I 10A, Type G 13A)
Single+Double portafilter	1+3	1+2	1+2	1+1

NOTE: Please check your regional price list for available versions/options and part numbers.

INSTALLATION NOTE: Please refer to the User Manual and the Technical Manual.



Welbilt reserves the right to make changes to the design or specifications without prior notice.