

ZIRCON

TRADITIONAL ESPRESSO

Models

- Zircon 3GR
- Zircon 2GR
- Zircon Mini 2GR
- Zircon Mini 1GR
- Zircon 2GR with grinder
- Zircon Mini 1GR with grinder



Zircon 3GR



Zircon 2GR



Zircon Mini 2GR



Zircon Mini 1GR

Description

Reliable and durable

The Zircon is the perfect espresso machine for those who need reliability in an essential model.

Hand built by skilled professionals, with only the best quality components, this machine demonstrates CREM's strong attitude towards quality craftsmanship and technology. User friendly features include: illuminated keypad buttons to control the dose of coffee, double pre infusion system, steam pressure gauge, automatic boiler refill and back-flush program for each group.

The electronic switchboard helps control the dosage of coffee through 5 selection buttons, located above each group. These allow you to dispense the right amount of coffee at the push of a button.

Features

- Volumetric dosing (5 button keypad)
- Double Pre infusion
- Automatic cleaning
- 2GR and Mini 1GR with built-in grinder versions available

Options

- Extra steam wand (Except Zircon 3gr)
- TA Version (High group)



Zircon 2GR with grinder



Zircon Mini 1GR with grinder

Technical specifications



	Zircon 3GR	Zircon 2GR	Zircon 2GR with grinder	Zircon Mini 2GR	Zircon Mini 1GR	Zircon Mini 1GR with grinder
Height, width, depth	530, 980, 590 mm 22, 38.5, 23"	530, 680, 590 mm 22, 27, 23"	630, 680, 590 mm 25, 27, 23"	530, 460, 590 mm 22, 18, 23"	530, 460, 590 mm 22, 18, 23"	630, 460, 590 mm 25, 18, 23" (incl. bean hopper)
Weight	65 Kg 143 lb	45Kg 99 lb	57Kg 126 lb	40.5 Kg 89 lb	35.5 Kg 104 lb	47 103.6 lb
Power ratings	380-415V 2N~ 4350W 50-60Hz	220-240V~ 3350W 50-60Hz	380-415V 2N~ 3700W 50-60Hz	220-240V~ 2800W 50-60Hz	220-240V~ 2800W 50-60Hz	220-240V~ 3150W 50-60Hz
Boiler(s) capacity	17.5 l	11.5 l	11.5 l	6 l	6 l	6 l
Operation pressure	0.8 to 1.2 bar	0.8 to 1.2 bar	0.8 to 1.2 bar	0.8 to 1.2 bar	0.8 to 1.2 bar	0.8 to 1.2 bar
Water connection	3/8" Internal thread	3/8" Internal thread	3/8" Internal thread	3/8" Internal thread	3/8" Internal thread	3/8" Internal thread
Noise level	<70dB	<70dB	<70dB	<70dB	<70dB	<70dB
Heating element	4000W	3050W	3050W	2500W	2500W	2500W
Steam wands+HW tap	2+1	1+1	1+1	1+1	1+1	1+1
Pressure gauge	Single 60 mm	Single 60 mm	Single 60 mm	Single 40 mm	Single 40 mm	Single 40 mm
Special customization	On request (MOQ)	On request (MOQ)	On request (MOQ)	On request (MOQ)	On request (MOQ)	On request (MOQ)
Single+Double portafilter	1+3	1+2	1+2	1+1	1+1	1+1

Standard Features

- Pressure switch control
- Volumetric dosing (5 button keypad)
- Rotary taps
- Built-in rotatory pump
- Soft pre infusion group chamber
- Electronic pre infusion
- Group auto cleaning cycle
- Black knobs

Options

- Extra steam wand (Except Zircon 3GR)
- Display versions available (PID controlled)
- TA Version

Zircon 2GR and Mini 1GR with grinder

- Automatic grinder
- 60 mm burrs
- 445 W motor featuring thermal protection. 1300 rpm
- Adjustable doses from 5 to 12 gr

NOTES:

- Zircon 2GR with grinder is PID controlled
- Zircon Mini 1GR with grinder features a pressure switch



ZIRCON

NOTE: Please check your regional price list for available versions/options and part numbers.

INSTALLATION NOTE: Please refer to the User Manual and the Technical Manual.

Welbilt reserves the right to make changes to the design or specifications without prior notice.